

Picture Tube

RECTANGULAR GLASS TYPE
LOW-VOLTAGE ELECTROSTATIC FOCUS

ALUMINIZED SCREEN
70° MAGNETIC DEFLECTION

Electrical:

Direct Interelectrode Capacitances:

Cathode to all other electrodes	5	pf
Grid No.1 to all other electrodes	6	pf
External conductive coating to anode.	$\left\{ \begin{array}{l} 750 \text{ max.} \\ 500 \text{ min.} \end{array} \right.$	pf
		ma
Heater Current at 6.3 volts	600 ± 60	ma
Electron Gun.	Type Requiring No Ion-Trap Magnet	

Optical:

Phosphor (For curves, see front of this section) . P4—Sulfide Type, Aluminized
 Faceplate, Cylindrical. Filterglass
 Light transmission (Approx.). 74%


Mechanical:

Weight (Approx.).	29 lbs
Overall Length.	23-1/32" ± 3/8"
Neck Length	7-1/2" ± 3/16"
Projected Area of Screen.	248 sq. in.
External Conductive Coating:	
Type.	Regular-Band
Contact area for grounding.	Near Reference Line

For Additional Information on Coatings and Dimensions:
 See *Picture-Tube Dimensional-Outlines and Bulb J170 A/C* sheets at front of this section

Cap	Recessed Small Cavity (JEDEC No. J1-21)
Base.	Small-Shell Duodecal (JEDEC Group 4, No. B6-63)
Basing Designation for BOTTOM VIEW.	12L

- Pin 1-Heater
- Pin 2-Grid No.1
- Pin 6-Grid No.4
- Pin 10-Grid No.2
- Pin 11-Cathode
- Pin 12-Heater



- Cap - Anode
 (Grid No.3,
 Grid No.5,
 Screen,
 Collector)
- C - External
 Conductive
 Coating

Maximum and Minimum Ratings, Design-Maximum Values:

Unless otherwise specified, voltage values are positive with respect to cathode

ANODE VOLTAGE	20000 max.	volts
GRID-NO.4 (FOCUSING) VOLTAGE:		
Positive value.	1100 max.	volts
Negative value.	550 max.	volts



21FP4D

GRID-No.2 VOLTAGE	550 max.	volts
GRID-No.1 VOLTAGE:		
Negative peak value	220 max.	volts
Negative bias value	155 max.	volts
Positive bias value	0 max.	volts
Positive peak value	2 max.	volts
HEATER VOLTAGE.	{ 6.9 max.	volts
	{ 5.7 min.	volts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode:		
During equipment warm-up period not exceeding 15 seconds.	450 max.	volts
After equipment warm-up period.	200 max.	volts
Heater positive with respect to cathode:		
Combined AC and DC voltage.	200 max.	volts
DC component.	100 max.	volts

Typical Operating Conditions for Grid-Drive Service:

Unless otherwise specified, voltage values are positive with respect to cathode

Anode Voltage	14000	volts
Grid-No.4 Voltage	-56 to +310	volts
Grid-No.2 Voltage	300	volts
Grid-No.1 Voltage for visual extinction of focused raster.	-28 to -72	volts

Maximum Circuit Value:

Grid-No.1-Circuit Resistance.	1.5 max.	megohms
---------------------------------------	----------	---------

For X-radiation shielding considerations, see sheet
X-RADIATION PRECAUTIONS FOR CATHODE-RAY TUBES
at front of this Section

